

### **HIGH-VOLUME SWING TUBE PISTON PUMP**



## RUGGED AND RELIABLE. EASY OPERATION. SIMPLE MAINTENANCE. CONCRETE & WET SHOTCRETE PUMP

The X-40D is our proven 6-inch by 39-inch swing tube piston pump designed for concrete pumping (up to 1.5-inch aggregate mixes) and wet shotcrete applications. The X-40D is user-friendly, easy to operate and simple to maintain. This machine is equipped with our rugged receiving hopper agitator, forklift tubing mounted to the lower hopper for easy flat pack removal and reliable solid-state electronics. The pump is equipped with four crane-lifting eyes and a wireless remote control for ease of operation.

PUMP UP TO 1.5"
AGGREGATE

#### HIGH-VOLUME SWING TUBE PISTON PUMP

# X-40D

#### **Features**

Robust 6-inch x 39-inch (150 mm x 1,000 mm) swing tube pumping system

1,000 psi piston face pressure for rugged pump cast and shotcrete applications

Easy flat pack removal with forklift pockets mounted to lower hopper

Reliable solid-state electronics



**Easy to Use Controls** 



Mecbo Pulsar Pumping System

#### **Applications**

Concrete Pumping Up To 1.5 in. (38 mm) Aggregate

**Wet Shotcrete** 

#### **Options**

**Auto Lubrication System** 

12 VDC Screen Vibrator

#### **Power Options**

72 HP Yanmar 4TNV98CT-NKW Water Cooled Diesel (No DEF)

74 HP Deutz TD2.9 Water Cooled Diesel (No DEF)

75 HP Electric Motor



#### **Specifications**

Pump	6 in. x 39 in. (150 mm x 1,000 mm) Swing Tube Piston Pump
Pumping Pressure	1,000 psi (69 bar)
Output	0-40 yd³/hr (0-30 m³/hr)
Discharge	5 in. (127 mm)
<b>Hopper Capacity</b>	11 ft <sup>3</sup> (0.31 m <sup>3</sup> )
Crane Pickup	4 Crane Lifting Eyes
Electrical	Solid State Value Control
Wireless Remote Control	Yes
Dimensions (L x W x H)	174 in. (4.42 m) x 76 in. (1.93 m) x 91 in. (2.31 m)
Weight	7,080 lbs. (3,211.43 kg)
Trailer	Single 8,000 lb. (3,628.74 kg) Capacity Axle with Electric Braking & Lights

**blastcrete.com 800.235.4867** | **+1.256.235.2700** 2000 Cobb Avenue, Anniston, AL 36201

